



NOTES:
SPECIFICATION:

- CURRENT RATING: 5.0A MAX
- VOLTAGE: 100 VAC
- TEMPERATURE RANGE: -30 °C ~ 85 °C
- CONTACT RESISTANCE: 40 MILLIONHM MAX
- INSULATION RESISTANCE: 100 MEGOHMS MIN.
- INSERTION FORCE : 5N~20N
- UNMATING FORCE: 8N~20N
- DURABILITY: 10,000 CYCLES

PIN	Signal Name	PTN	Signal Name
A1	GND	B12	GND
A2		B11	
A3		B10	
A4	VBUS	B9	VBUS
A5	CC1	B8	SUB2
A6	Dp1	B7	Dn2
A7	Dn1	B6	Dp2
A8	SUB1	B5	CC2
A9	VBUS	B4	VBUS
A10		B3	
A11		B2	
A12	GND	B1	GND

3	SHELL	STAINLESS STEEL	Plated	IPCS
2	C-TACT	COPPER ALLOY	Plated	IPSET
1	H-USB-6	HIGH TEMPERATURE PLASTIC	BLACK	IPCS
MATERIAL				
品名				
單位				
日期				
編號				
圖號				
設計				
審核				
校核				
比例				
版次				
圖號				
設計				
尚學林				

第三角視角
公差:
X. ±0.20 X° 3°
.X ±0.10 .X° 1°
.XX ±0.05 .XX

US03: 1.1TV版/0.05母座式16P
MM 1:1
2016.11.25
SHK-31021

深圳市順宏康科技有限公司