



NOTES:

- Housing: Thermoplastics, UL94V-0
- Contact: Copper Alloy
- Shell: Copper Alloy/Steel
- Voltage Current Rating: 1.5 AMP, 30V AC
- Insulation Resistance: 1000MΩ Min.
- Contact Resistance: 30 MΩ Max.
- Dielectric Withstanding Voltage: 500W AC
- Temperature Range: -35°C to +85°C
- Insulator color: Black/White
- Plastic material: PBT/LCP/Others
- Shell finish: Nickel plated/Tin-Lead plated
- Mechanical:
- Mating Force: 3.5KG MAX
- Umating Force: 0.7 KG MIN.
- Contact finish:
- 01: Selective Gold Flash
- 02: Selective Gold 3U”
- 03: Selective Gold 5U”
- 04: Selective Gold 15U”
- 05: Selective Gold 30U”

目錄 MAPX	變更內容 MODIFICATION	日期 DATE
------------	----------------------	------------

产品图
PRODUCT CHART DWG

深圳市顺宏康科技有限公司

公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	产品料号 PRODUCT PART NO.	SHK-20078
X	±0.15	X'	±5'	审核 CHECK	产品名称 PRODUCT NAME	USB-A17沉板
.XX	±0.10	.X'	±2'	日期 DATE	角注 VIEW	
.XXX	±0.05	.XX'	±1'	核准 APPR	版本 VER	A0
	±0.03	.XXX'	±0.5'			