

PCB LAY-UT
(B-T-M VIEW)

规格说明: Specification:
电气特性: Electrical:


- 1 额定电流: Current Rating: 5A/Contact terminal
- 2 额定电压: Voltage Rating: 30V DC
- 3 接触阻抗: Contact Resistance: 30 milliohms MAX
- 4 耐压: Dielectric Withstanding Voltage: 500 V AC AT Sea Level
- 5 绝缘阻抗: Insulation Resistance: 1000MEGA ohms MIN

物理性能: Mechanical:

- 1 插拔力: Contact Mating Force: 3 57kgf (MAX) UHmate Force: 1 02kgf (MIN)
- 2 端子保持力: Terminal Retention: 1 2kgf (MIN)

原材料: Material:

- 1 塑胶: Housing: High Temperature Thermoplastics, UL 94V 0 PBT White/Black
 - 2 端子: Contact: Copper Alloy C2680
 - 3 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
- 1 端子: Contact: Plated Gold Plating Area; Thickness: 10µm
 - 2 外壳: Shell: Nickel Plating



深圳市顺宏科技有限公司

品名 (ITEM NO)	SHK-20083	图号 (DWG NO)	A/0	单位 (UNIT): MM
料号 (PART NO)	A008-1I	版本 (REV)		比例 (SCALE) 1:1
型号 (MODEL NO)		日期 (DATE)		
		设计 (DESIGN)		未注公差 TOLERANCE UNSPECIFIED
		审核 (CHECKED)		X.X ±0.30
		核准 (APPROVED)		X.XX ±0.20
				X.XXX ±0.10
				X° ±5°
				X.X° ±2°