



?	?	?	?	?	?	?	?	?	?
Max	?	?	?	?	?	?	?	?	?
Δ	?	?	?	?	?	?	?	?	?
Modification	Date	Draw	Approve						

规格说明: Specifications:

电气特性: Electrical:

- 1. 额定电流: Current Rating  
1.5A/contact terminal
- 2. 额定电压: Voltage Rating  
30V DC
- 3. 接触电阻: Contact Resistance  
30 milliohms MAX
- 4. 额定电压: Dielectric Withstanding Voltage:  
500 V AC AT Sea Level
- 5. 绝缘电阻: Insulation Resistance:  
1000MEGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force  
Mate force: 3.57kgf(MAX)  
Umate force: 1.02kgf(MIN)
- 2. 端子保持力: Terminal Retention  
1.0kgf(MIN)

原材料: Material:

- 1. 塑胶: Housing:  
Hing Temperature Ternmaplastics,
- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 1. 端子: Contact: Plated Gold in Mating Area;  
Tin On Solder Tails
- 2. 外壳: Shell:  
铜壳四周镀 80U"(MIN) 镍  
铜壳四周镀 80U"(MIN) 镍

Nickel Plating

深圳市顺宏康科技有限公司

MANUFACTURE DWG	公差一律按表	DATE	DATE	CHECKED	核准	APPROVE	批准	SCALE	比例	UNIT	单位	DRAWING NO.	图号	DWGNO.	版本号	VER	SHEET	页数	PG1
TOLERANCE UNLESS OTHERWISE																			
X±0.15	X±5'																		
XX±0.05	.X±2'																		
XXX±0.02	.XX±1'																		