



RECOMMEND P. C. B. LAYOUT

REV	LTR	DESCRIPTION	DATE	APPROVED
A0		依新料号编码原则发行图面	20101125	zhacaci

NOTES:
1. MATERIAL SPECIFICATION:

- 1) HOUSING MATERIAL:SEE PART NO.
 - 2) SHELL MATERIAL:SEE PART NO. T:0.35mm PLATING:SEE PART NO.
 - 3) BACK COVER MATERIAL:SPCC T:0.35mm PLATING:NICKE.
 - 4) SHRAPNEL MATERIAL:SEE PART NO. T:0.25mm
 - 5) TERMINAL: COPPER ALLOY T:0.25mm PLATING:SEE PART NO.
2. ELECTRICAL CHARACTERISTIC:
- 1) VOLTAGE CURRENT RATING: 1AMP, 30V DC;
 - 2) INSULATION RESISTANCE: 1000MΩ MIN;
 - 3) CONTACT RESISTANCE: 30mΩ MAX;
 - 4) WITHSTANDING VOLTAGE: 500V AC;

3. MECHANICAL:

- 1) MATING FORCE:3.57 KG MAX
- 2) UNMATING FORCE:1.02 KG MIN.

4. 02-1X XAX X XNX X XN-001

1 2 3 4 5 6 7 8

1:外壳材质代码: A:黄铜C2680, B:磷铜C5191,

D:单光铁 E:双光铁

2:外壳电镀代码: A:镀镍12H, B:镀镍24H, C:镀镍48H, D:镀雾镍

3:中夹片材质及电镀代码:A:SPCC 镀镍 E:黄铜 镀镍

I:磷铜 镀镍 K:不锈钢

L:不锈钢 镀镍

4:主体胶芯材质代码: A:PBT, B:LCR F:PA66

5:主体胶芯颜色代码: 1:白色 2:黑色 3:本色

6:端子材质代码: 1:黄铜C2680, 2:磷铜C5191,

7:端子电镀代码: A:半金锡G/F, B:半金锡3u",

C:半金锡15u", D:半金锡30u",

E:半金雾锡G/F, F:半金雾锡3u",

G:半金雾锡15u", H:半金雾锡30u".

8: 环保代码: N:非环保, R:ROHS, S:SONY, F:ROHS+无卤

深圳市顺宏康科技有限公司

UR A F双层全包长穿脚无弹

PART NO.: SHK-20102

DRAWING NO.: 021-001

TOLERANCES	
.X	±0.30
.XX	±0.20
.XXX	±0.10
ANGLES	±3.00°

APPD:	
CHECK:	
DRAWN:	越群 20101125

REV:	A/0	SIZE:	A4	UNIT:	M M	SCALE:	1:1	SHEET:	1/1
------	-----	-------	----	-------	-----	--------	-----	--------	-----