

项目 Mdx	变更内容 Modification	日期 Date	修改人 Draw	核准 Approve

规格说明: Specifications:
电气特性: Electrical:

- 额定电流: Current Rating
3.1A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触电阻: Contact Resistance
30 milliohms MAX
- 耐压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料: Material:

- 塑壳: Housing:
Hing Temperature Thermoplastics,

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Talls
- 外壳: Shell:
端子四周镀50U”(MIN)镍,镀金区域镀100—200U”镀金1U”

Nickel Plating

深圳市顺宏康科技有限公司

公差 TOLERANCE UNLESS OTHERWISE SPECIFIED	日期 DATE	图号 DRAWING NO.	图名 DRAWING NAME
X±0.20	2017.06.20	SHIK-30115	四脚卷边插座
XX±0.10			
XXX±0.05			

