



實跡外觀: Specification:
長 短

- 1 塗層: 1.5A/contact terminal
- 2 塗層: 30V DC
- 3 塗層: 30 milliohms MAX
- 4 塗層: 500 V AC AT Sea Level
- 5 塗層: 1000MEGA ohms MIN

易熔合金: Mechanical:

- 1 層壓: 3.57kgf(MAX)
3.57kgf(MIN)
- 2 傷熱: 1.02kgf(MIN)
1.2kgf(MIN)

焊料: Material:

- 1 噴漆: Temperature: PBT White/Black
- 2 傷熱: Copper Alloy C2680
- 3 塗層: Copper Alloy C2680/SPCC

鍍層: Finish:

- 1 傷熱: Plated Gold
Tin On Solder Tails
- 2 塗層: Nickel Plating

RECOMMENDED P. C. B. PATTERN LAY OUT



深圳市顺宏康科技有限公司

DRAWN H.Q.huocuy APPROVED	UNIT MM	USB AF 双层直插17.0MM弯脚直边	
		SCALE 3/1	PART NO. SHK-20130
DATE 2011.03.18	SIZE A4	DOC. NO.	REV. A

UNLESS OTHERWISE SPECIFIED TOLERANCE
.X ±0.20
.XX ±0.15
.XXX ±0.10
ANG. ±2°