



PCB LAYOUT

规格说明:Specifications:
电气特性:Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触电阻: Contact Resistance
30 milliohms MAX
4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘电阻: Insulation Resistance:
1000MΩ ohms MIN

物理性能:Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force:3.57kgf (MAX)
Unmate force:1.02kgf (MIN)
2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料:Material:

1. 塑胶:Housing:
Hing Temperature Thermoplastics,
UL 94V-0 PBT White/Black
2. 端子:Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

1. 端子:Contact: Plated Gold in Mating Area:
Tin On Solder Tails
2. 外壳:Shell:
Nickel Plating

深圳市顺宏康科技有限公司				图号 (DWG NO)		单位 (UNIT): MM
品名 (ITEM NO)	AK 180 度 13.7 号 扁平口	版本 (REV)	A/0	日期 (DATE)	2016. 06. 08	比例 (SCALE) 1:1
料号 (PART NO)	SHK-20073	设计 (DESIGN)	李碧波	审核 (CHECKED)		未注公差 FRACTIONAL DIM ±0.30 ±0.25 ±0.10 ±0.05
模号 (MODEL NO)	ZD-006	核准 (APPROVED)				