

?	?	?	?	?	?	?	?
Max	Modification	Date	Draw	Approve			
A							

规格说明:Specifications:

电气特性:Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触电阻:Contact Resistance
30 milliohms MAX
- 耐压:Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘电阻:Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料:Material:

- 塑胶:Housing:
Hing Temperature Ternmaplastics,
- 端子:Contact:Copper Alloy C2680
- 外壳:Shell: Copper Alloy C2680/SPCC

电镀:Finish:

- 端子:Contact: Plated Gold in Mating Area:
Tin On Solder Tails
- 端子四周镀50U"(MIN)锡,镀金区域镀100—200U"镀金1U"

2.外壳:Shell:

铜壳四周镀80U"(MIN)锡

Nickel Plating

深圳市顺宏康科技有限公司

成品图		公差		日期		单位		制图		审核		批准		版本		页次	
MANUFACTURE DWG		X.±5"		DATE		UNIT		DRAWING		DESIGN		APPROVE		VER		SHEET	
TOLERANCE UNLESS OTHERWISE		XX±0.05		CHECKED		SCALE		NAME		DESIGN		NEW		PG1			
XXX±0.02 .XX±1"																	

