

规格说明: Specifications:

电气特性: Electrical:

1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗: Contact Resistance
30 milliohms MAX

4. 耐压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:


1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.75kgf (MAX)
Umate force: 1.02kgf (MIN)
2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Thermoplastics,
U1 94V-0 PBT/LCP White/Black
2. 端子: Contact: Copper Alloy C2680
3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Talls
 2. 外壳: Shell:
Nickel Plating

注: ▼为重点管控尺寸

深圳市顺宏康科技有限公司



品名 (ITEM NO)	AM 苹果无缝焊线式			图号 (DWG. NO)		单位 (UNIT):	MM
料号 (PART NO)	SHK-20298			版本 (REV)	A/0	比例 (SCALE)	1:1
型号 (MODEL NO)		设计 (DESIGN)	王文东	日期 (DATE)	2014.07.10	公差	±0.30
		审核 (CHECKED)				公差	±0.20
		核准 (APPROVED)				公差	±0.10
						公差	±5°
						公差	±2°